



Turn to the experts

Residential and light commercial

# SPLIT SYSTEMS CONSOLE






CONSOLE- R-32 - 38QUS / 42QZY



CONSOLE  
38QUS / 42QZY

- Can be installed standing on the floor, or wall-mounted
- **Unobtrusive design** can easily fit into most interiors with different decorating-schemes
- **Compact design**
- **Dual airflow outlets with large dimension** satisfy both cooling and heating needs in different seasons and allow a quick comfort of the room
- **Good option for heater replacement**
- Smart humidity control
- Infrared remote controller as standard
- Compatible with mono and multi-split system
- Wi-Fi control as option with Smart Kit



Accessories



Specifications 42QZY Console



		1 phase	
		SIZE 12	SIZE 18
<b>CONSOLE SYSTEM</b>			
Cooling capacity	KW	3.70 (0.77-4.25)	4.90 (2.64-5.57)
Heating capacity	kW	4.00 (0.46-4.70)	5.20 (2.20-6.30)
Heating capacity at -7, -10, -15°C	kW	3,00 - 2,60 - 2,30	4,50 - 3,90 - 3,50
P design capacity cooling	kW	3,74	4,90
P design capacity heating (average)	kW	2,60	4,20
P design capacity heating (warmer)	kW	3,20	5,00
SEER/SCOP(average)/SCOP(warmer)	W/W	7.7 / 4.2 / 5.7	7.1 / 4.2 / 5.1
Energy Label	-	A++ / A+ / A+++	A++ / A+ / A++
Yearly energy consumption	kWh	168 / 867 / 786	242 / 1400 / 1373
EER/COP	W/W	3.66 / 4.04	3.31 / 3.59
Standard current (cooling)	A	4,50	6,7
Standard input (cooling)	W	1010	1480
Standard current (heating)	A	4,70	6,4
Standard input (heating)	W	990	1450
<b>OUTDOOR UNIT</b>		<b>38QUS012D8S-1</b>	<b>38QUS018D8S-1</b>
Temperature range cooling	°C	-15-50	-15-50
Temperature range heating	°C	-15-24	-15-24
Voltage/Hz/Ph	-	220-240V / 50Hz / 1Ph	220-240V / 50Hz / 1Ph
Rated current	A	9,0	13,5
Rated input	W	1850	2950
Refrigerant amount (R-32)	kg/TCO2	0.72 / 0.486	1.15 / 0.776
Liquid side/Gas side	mm(inch)	Ø6.35 / Ø9.52 (1/4" / 3/8")	Ø6.35 / Ø12.7 (1/4" / 1/2")
Standard piping length	m	5	5
Min. piping length	m	3	3
Max. piping length	m	25	30
Max. difference	m	10	20
Additional charge	g/m	12	12
Sound power level	dB(A)	62	65
Sound pressure level	dB(A)	54	59
Airflow	m³/h	2200	2100
Weight (Net/Gross)	kg	26.6 / 29.0	32.5 / 35.2
Dimensions (WxDxH)	mm	765 x 303 x 555	805 x 330 x 554
Packing (WxDxH)	mm	887 x 337 x 610	915 x 370 x 615
<b>INDOOR UNIT</b>		<b>42QZY012D8S</b>	
Indoor fan motor input	W	64	64
Indoor fan motor max current	A	0,62	0,62
Sound power level	dB(A)	54	55
Sound pressure level (high/med/low)	dB(A)	37 / 34 / 27	41.0 / 38.0 / 32.0
Air flow (high/med/low)	m³/h	650 / 580 / 490	780 / 690 / 600
External static pressure	Pa	0	0
Weight (Net/Gross)(Body)	kg	14.9 / 18.8	15.0 / 19.0
Weight (Net/Gross)(Panel)	kg	/	/
Dimensions (WxDxH)(Body)	mm	794 x 200 x 621	794 x 200 x 621
Packing (WxDxH)(Body)	mm	865 x 280 x 719	865 x 280 x 719

Note  
\* Sound data @ cooling mode

Multi-split combination

		OUTDOOR UNIT						
		2 OUTPUTS		3 OUTPUTS		4 OUTPUTS		5 OUTPUTS
		14	18	21	27	28	36	42
		38QUS014D8S2	38QUS018D8S2-1	38QUS021D8S3	38QUS027D8S3-1	38QUS028D8S4	38QUS036D8S4-1	38QUS042D8S5-1
INDOOR UNIT	12	●	●	●	●	●	●	●
	18			●	●	●	●	●



[www.carrier.com](http://www.carrier.com)

Carrier is committed to continuously improving its products to ensure the highest quality and reliability standards, and to meet local regulations and market requirements. All features and specifications are subject to change without prior notice. All trademarks and service marks referred herein are property of their respective owners. ©2023 Carrier. All Rights Reserved.  
Photo credit: Adobestock

01/2023 B-RLC-024-LEAFLET CONSOLE 42QZY



Turn to the experts